



Enviro Science Technologies

Aqua Cure - 30

Product:

Aqua cure 30 is a concentrated curing and sealing compound, composed of “state-of-the-art” true water base resins compound.

Features:

- *Water base voc compliance.
- *Can be diluted with water for lower percentage solids, for proper

Applications:

- *Non-yellowing UV stable.
- *Skid resistance, dries tack free.
- *Will minimize hairline and premature cracking, dusting and spalling.
- *Long lasting protection for new and old concrete.

Uses:

Aqua cure-30 is use for cure, seal, and dust proof new and old, interior and exterior, Vertical and horizontal concrete surfaces, such as, commercial and industrial floors, sidewalks, basement, and garage floors, multi-level parking decks, patios, driveways and parking areas. Aqua Cure-30 can be use straight wherever a thick film, high gloss, sheen finish is desired. See dilution chart below for proper applications.

Specifications:

ASTM - C 309 Type 1, class B
ASTM - C 1315
AASH TO M-148 Type - 1, class B

Technical Data:

Total Solid -	30% concentrate
Weight/gallon -	8.50 #gal
PH -	8.5 - 9.5
Solubility in water -	Yes
Appearance/odor -	Milky - normal resin smell

Dilution:

For light sheen: use 10% dilution of Aqua Cure-30.
For medium sheen: use 15% dilution of Aqua Cure-30.
For high sheen: Use straight Aqua Cure 30 for high gloss.

Aqua Cure – 30 (Continued)

Note:

For most concrete, use 10 to 15% dilution when properly applied, Aqua Cure-30 yields superior curing efficiency. However good concrete and good concreting practice should be used as is. This product is not a cure-all for improperly mixed or placed concrete.

Application:

Make proper dilution of Aqua Cure-30 before using. Use a typical commercial sprayer for efficient application. Aqua Cure-30 should be sprayed on with an 8001 tip in a fine fog pattern without spurts and dribbles. If puddles occur, brush or roll them out. Aqua Cure-30 may also be applied with a nap roller, soft bristle broom or lambs wool applicator.

Packaging:

1 gal, 5 gal bucket and 55 gal drums.

Bulk Packaging:

275 gal, mini bulk tote tank.

Applicators Guide:

Read helpful application tips before using this product.

Limited Warranty:

EST has no control over the storage, handling or use of this product, thus the guarantee is limited to the purchase price of the defective material only.